

BS410 : SURFACE MOUNT SPEAKER

It is constructed with high quality ABS plastic with 4" dual cone speaker driver and multi tapping matching transformer of 1 / 3 / 6 and 10W 100 V line. Suitable for wall and ceiling installation with optional tilt mounting bracket. Available in white colour.

Packing information

BS410 : 550 (W) x 215 (H) x 420 (D) mm
 : 14.5 kg
 : 12 uts per carton

DV410 : SURFACE MOUNT SPEAKER

A classic yet favourite model which is suitable for installations in small enclosed areas such as staircase, office, etc. Available in white colour with multi tap matching transformer of 1 / 3 / and 6W 100V line, fit for vertical or horizontal installations.

Packing information

DV410 : 590 (W) x 400 (H) x 303 (D) mm
 : 15.4 kg
 : 18 uts per carton

CH700 SERIES COLUMN SPEAKER

Built ruggedly with aluminum die cast housing and available in 3 power rating of 20 / 30 and 40W 100V line with half or full power tapping. Suitable for classrooms, hyper markets, mosques, etc.

Packing information

CH720 : 510 (W) x 363 (H) x 300 (D) mm
 : 7.8 kg
 : 2 uts per carton

CH730 : 683 (W) x 473 (H) x 306 (D) mm
 : 9.0 kg
 : 2 uts per carton

CH740 : 802 (W) x 563 (H) x 389 (D) mm
 : 11.0 kg
 : 2 uts per carton

SURFACE MOUNT & COLUMN SPEAKER

4" 10W 100V LINE | **BS410**

4" 6W 100V LINE | **DV410**

20 - 40W 100V LINE COLUMN SPEAKER | **CH700**

BS410
4" 10W 100V



DV410
4" 6W 100V



CH740 40W 100V

CH730 30W 100V

CH720 20W 100V



TECHNICAL SPECIFICATIONS :

	BS410	DV410	CH720	CH730	CH740
SPEAKER					
Power rating	10W 100V	6W 100V	20W 100V	30W 100V	40W 100V
Diameter	4"		2 x 4"	3 x 4"	4 x 4"
Cone type	Dual cone				
Impedance	8 Ohm				
Freq response (+/- 5dB)	100 ~ 16 KHz	100 ~ 18 KHz	85 ~ 15 KHz	80 ~ 15 KHz	75 ~ 15 KHz
SPL @ 1W / m (+/- 3dB) 1 KHz	92 dB	90 dB	91 dB	93 dB	95 dB
Magnet weight	7.5 oz	3.0 oz	7.5 oz		
TRANSFORMER					
Tapping (100V line)	1 / 3 / 6 / 10W	1 / 3 / 6W	10 / 20W	15 / 30W	20 / 40W
Primary impedance (Ohm)	10 K / 3.3 K / 1.6 K / 1 K	10 K / 3.3 K / 1.6 K	1 K / 500 Ohm	660 / 330 Ohm	500 / 230 Ohm
Secondary impedance	8 Ohm				
PHYSICAL					
Grille / enclosure	ABS with metal grille		Aluminum / metal grille		
Overall size (WxHxD) mm	185 x 205 x 90	195 x 215 x 105	145 x 400 x 100	145 x 495 x 100	145 x 605 x 100
Weight	1.1 kg	750 g	3.2 kg	3.7 kg	4.6 kg
Colour	White		Dark grey / front black grille		