

MUSIC & ARRAY SPEAKERS

LA4100 | 120W 100V ARRAY

FS338 | 4" 40W 100V LINE

FS340 | 4" 40W 100V LINE

FS338 40W 100V FULL RANGE



FS340 40W 100V FULL RANGE



LA4100 120W 100V LINE ARRAY

FS338 : FOREGROUND MUSIC SPEAKER

FS338 is built as multi purpose speaker, optimising the features of smooth and pleasant outlooks while maintaining the audio performance. Thus by its appearance and sound quality, it can be employed in most indoor venues.

It is driven by 2 x 4" PP speakers and a 1" tweeter with 40W 100V line power. It can also be driven directly from audio amplifier with 4 Ohm connections. Multiple power tapping is available via the rotary switch from 5 to 40W 100V line.

Installation is rather flexible due to its dual angle mounting bracket. They can be mounted in horizontal or vertical position. If wider coverage is required, then can be installed in horizontal array format, with two, three or 360 degree format via the optional mounting pole.

Packing information

FS338 : 440 (W) x 435 (H) x 360 (D) mm
 : 18.2 kg
 : 4 uts per carton

FS340 : FOREGROUND MUSIC SPEAKER

FS340 delivers smoothing sound with its 4" driver with tweeter. Available in 40W 100V line with power selector for level adjustment to suit area of installation. It can be installed vertically or horizontally, thanks to its flexible mounting bracket.

Be it a restaurant, pub or cafe, meeting room or lobby, FS340 shall be the exact candidate to choose from.

Packing information

FS340 : 455 (W) x 384 (H) x 240 (D) mm
 : 7.8 kg
 : 2 uts per carton

LA4100 : CABINET ARRAY SPEAKER

LA4100 is array speaker built with 4" driver delivering a punch of 120W of output with dispersion angle of H120 x V60 degree and high SPL. Most suitable for application like mosques, halls, public areas such as bus stations, airports, etc where speech clarity is utmost important.

Packing information

LA4100 : 485 (W) x 665 (H) x 275 (D) mm
 : 21 kg
 : 2 uts per carton

TECHNICAL SPECIFICATIONS :

	FS338	LA4100	FS340
SPEAKER			
Power rating	40W 100V max 60W	120W 100V	40W 100V 60W
Driver	2 x 4", 1" PZ tweeter	4 x 4"	2 x 4", 1" PZ tweeter
Diameter	4"		
Cone type	Single cone		
Impedance	8 Ohm (4 Ohm total)	8 Ohm	
Freq response (+/- 5dB)	70 ~ 16 KHz	130 ~ 18 KHz	70 ~ 16 KHz
SPL @ 1W / m (+/- 3dB) 1 KHz	87 dB	96 dB	88 dB
TRANSFORMER			
Tapping (100V line)	5 / 10 / 20 / 40W	30 / 60 / 120W	5 / 10 / 40W / 80hm
Primary impedance (Ohm)	2 K / 1 K / 500 / 250 Ohm	167 / 83 Ohm	2K / 1K / 250 / 8 Ohm
Secondary impedance	4 Ohm	8 Ohm	
PHYSICAL			
Grille / enclosure	Black metal / ABS	Black metal / Polypropylene (PP)	Black metal / ABS
Mounting	Vertical / Horizontal	Vertical	Vertical / Horizontal
Overall size (WxHxD) mm	137 x 385 x 262	205 x 585 x 195	209 x 345 x 218
Weight	3.4 kg	10 kg	3.3 kg
Colour	Black		